



Model with basic equipment.

Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Universal voltage
- Screw-in Terminal / plug-in connection
- Compatible with current mortise locks
- Compatible with ProFix® 2 striking plates
- Optimized sliding ramp for a smooth interplay with latch bolt
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Technical data	
Voltage	10-24 V AC/DC
DIN direction	Universal
Adjustable latch (FF, FaFix®)	Yes
Fail-locked	Yes
Break-in resistance	3750 N
Height	66 mm
Width	20,1 mm
Depth	25,5 mm
FaFix® adjustment range	3 mm
Latch bolt engaging depth	5,5 mm
Operating temperature range	-15 °C to +40 °C
Installation position	vertical and horizontal
Load cycles for in-plant test	250000
Suitability for fire protection	No
Continuous duty	11-13 V DC
Rated resistance	43 Ohm
Rated current consumption 12 V DC	280 mA
Rated current consumption 24 V DC	560 mA
Rated current consumption 12 V AC	250 mA
Rated current consumption 24 V AC	500 mA
Max. latch preload AC	200 N
Max. latch preload DC operation 24 V	> 350 N (24V)
Max. latch preload DC (stabilised)	50 N
Max. latch preload DC (stabilised) 24 V	200 N (24V)

EAN-Number	Article number
4042203354135	118.13-----A71