

The MEDIATOR multi-point lock is available with different backsets in its tubular frame version.

Overview of Advantages

- Self-locking system: Bolt and latch are blocked - More effectively secured
- Additional sturdy hooked bolts for improved burglary protection. The hooked bolts are not designed to apply pressure to door seals. The system will only work effectively if there is no side pressure on the bolt.
- Mechanical follow up control between double action latch and control latch
- Integrated panic function via internal door handle
- Alternative function for unlocking with key from outside
- Short backset behind for tubular frame version: 15 mm

Scope of delivery

- 1 MEDIATOR multi-point lock

Technical data	
Backset	35 mm
Distance	Euro profile cylinder: 92 mm
Bolt throw	20 mm
Follower	9 mm (included in supply: reducer to 8 mm)
U face plate	24 x 6.5 x 1,760 mm
Standards	DIN EN 179 CE Certificate of Conformity 0432-BPR-001, DIN EN 1125 in pipeline, VDS certification applied for

Article number	629X200PZ-----1
----------------	-----------------



MEDIATOR multi-point lock 629X500PZ-----1



The MEDIATOR multi-point lock is available with different backsets in its wooden and steel door version.

Scope of delivery

- 1 MEDIATOR multi-point lock

Technical data	
Backset	55 mm
Distance	Euro profile cylinder: 72 mm
Bolt throw	20 mm
Follower	9 mm (included in supply: reducer to 8 mm)
U face plate	24 x 6.5 x 1,760 mm
Standards	DIN EN 179 CE Certificate of Conformity 0432-BPR-001, DIN EN 1125 in pipeline, VDS certification applied for

Article number	
	629X500PZ-----1

