


Fast assembly concealed hinge

- ▶ Sensys wide angle hinge, with zero protrusion
- ▶ 165° opening angle, drilling pattern TH 52 x 5.5 mm



- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness of 15 - 32 mm
- ▶ Cup depth 11.6 mm
- ▶ Integrated overlay adjustment +2 mm / -2 mm
- ▶ Integrated depth adjustment +3 mm / -2 mm
- ▶ Height adjustment at mounting plate
- ▶ Steel/nickel plated die-cast zinc

Drilling pattern



full overlay
(Base B 12.5 mm)



half overlay
(Base B 3 mm)



With integrated Silent System, with self closing feature (Sensys 8657i)

Cup assembly	Mounting hole ø x T mm	full overlay 1/50 ea.	half overlay 1/50 ea.
for screwing on	-	9 099 540	9 099 550
for pressing in	ø 10 x 11	9 099 541	9 099 551
Fix fast assembly	ø 10 x 6	9 099 543	9 099 553
with expanding sockets	ø 10 x 11	9 099 546	9 099 556

Without Silent System, with self closing feature (Sensys 8657)

Cup assembly	Mounting hole ø x T mm	full overlay 1/50 ea.	half overlay 1/50 ea.
for screwing on	-	9 099 600	9 099 610
for pressing in	ø 10 x 11	9 099 601	9 099 611
Fix fast assembly	ø 10 x 6	9 099 603	9 099 613
with expanding sockets	ø 10 x 11	9 099 606	

Without Silent System, without self closing feature, for handleless applications (Sensys 8687)

Cup assembly	Mounting hole ø x T mm	full overlay 1/50 ea.	half overlay 1/50 ea.
for screwing on	-	9 099 660	9 099 670
for pressing in	ø 10 x 11	9 099 661	
Fix fast assembly	ø 10 x 6	9 099 663	9 099 673
with expanding sockets	ø 10 x 11	9 099 666	



hettich.com/short/bbf70