


Fast assembly concealed hinge

- ▶ Sensys wide angle hinge, with zero protrusion
- ▶ Opening angle 165°, drilling pattern TB 45 x 9.5 mm



- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness 15 - 32 mm
- ▶ Cup depth 11.6 mm
- ▶ Integrated overlay adjustment +2 mm / -2 mm
- ▶ Integrated depth adjustment +3 mm / -2 mm
- ▶ Height adjustment at mounting plate
- ▶ Steel / nickel plated die-cast zinc

Drilling pattern



full overlay (Base B 12.5 mm)



half overlay (Base B 3 mm)



With integrated Silent System, with self closing feature (Sensys 8657i)

Cup assembly	Mounting hole ø x T mm	full overlay	half overlay
		50 ea.	50 ea.
For screwing on	-	9 099 560	9 099 570
For pressing in	ø 8 x 11	9 099 561	9 099 571
Fix fast assembly	ø 8 x 6	9 099 563	9 099 573
with expanding sockets	ø 8 x 11	9 099 566	9 099 576

Without Silent System, with self closing feature (Sensys 8657)

Cup assembly	Mounting hole ø x T mm	full overlay	half overlay
		50 ea.	50 ea.
For screwing on	-	9 099 620	
For pressing in	ø 8 x 11	9 099 621	
Fix fast assembly	ø 8 x 6	9 099 623	9 099 633
with expanding sockets	ø 8 x 11	9 099 626	

Without Silent System, without self closing feature, for handleless applications (Sensys 8687)

Cup assembly	Mounting hole ø x T mm	full overlay	half overlay
		50 ea.	50 ea.
For screwing on	-	9 099 680	
Fix fast assembly	ø 8 x 6	9 099 683	9 099 693