


Fast assembly concealed hinge

- ▶ Sensys angle hinge W90
- ▶ Opening angle 95°, drilling pattern TB 45 x 9.5 mm



- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness 15 - 28 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated adjustment of door offset +1 mm / -2 mm
- ▶ Integrated reveal adjustment +3 mm / -2 mm
- ▶ Height adjustment at mounting plate
- ▶ Steel nickel plated

Drilling pattern



inset
(Base B 4 mm)



With integrated Silent System, with self closing feature (Sensys 8639i W90)

	Mounting hole ø x T mm	inset
Cup assembly		50 ea.
For screwing on	-	9 088 027
For pressing in	ø 8 x 11	9 088 045
Fix fast assembly	ø 8 x 6	9 088 081
with expanding sockets	ø 8 x 11	9 088 093

Without Silent System, with self closing feature (Sensys 8639 W90)

	Mounting hole ø x T mm	inset
Cup assembly		50 ea.
Fix fast assembly	ø 8 x 6	9 088 147

Without Silent System, without self closing feature, for handleless applications (Sensys 8669 W90)

	Mounting hole ø x T mm	inset
Cup assembly		50 ea.
Fix fast assembly	ø 8 x 6	9 088 223