

## Fast assembly concealed hinge

- ▶ Sensys thin door hinge, door thickness from 10 mm
- ▶ Opening angle 110°, drilling pattern TH 52 x 5.5 mm



- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness 10 - 19 mm
- ▶ Cup depth 7.8 mm
- ▶ Integrated overlay adjustment +2 mm / -2 mm
- ▶ Integrated depth adjustment +3 mm / -2 mm
- ▶ Height adjustment at mounting plate
- ▶ Steel in obsidian black

Drilling pattern	full overlay (Base B 12.5 mm)	half overlay (Base B 3 mm)	inset (Base B -4 mm)

### With integrated Silent System, with self closing feature (Sensys 8646i)

Cup assembly	Mounting hole $\varnothing \times T$ mm	full overlay 50 ea.	half overlay 50 ea.	inset 50 ea.
For screwing on	-	9 091 761	9 091 762	9 091 763
with expanding sockets	$\varnothing 10 \times 8$	9 091 793	9 091 794	9 091 795

### Without Silent System, without self closing feature, for handleless applications (Sensys 8676)

Cup assembly	Mounting hole $\varnothing \times T$ mm	full overlay 50 ea.	half overlay 50 ea.	inset 50 ea.
For screwing on	-	9 091 764	9 091 765	9 091 766
with expanding sockets	$\varnothing 10 \times 8$	9 091 796	9 091 797	9 091 798