


Fast assembly concealed hinge

- ▶ Sensys angle hinge W30
- ▶ Opening angle 95°, drilling pattern TH 52 x 5.5 mm



- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness 15 - 28 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated overlay adjustment +2 mm / -2 mm
- ▶ Integrated depth adjustment +3 mm / -2 mm
- ▶ Height adjustment at mounting plate
- ▶ Steel / nickel plated die-cast zinc

Drilling pattern



overlay
(Base B 2 mm)



inset
(Base B -16 mm)



With integrated Silent System, with self closing feature (Sensys 8639i W30)

Cup assembly	Mounting hole $\varnothing \times T$ mm	overlay	inset
		50 ea.	50 ea.
For screwing on	-	9 088 016	9 088 017
For pressing in	$\varnothing 10 \times 11$	9 088 034	
Fix fast assembly	$\varnothing 10 \times 6$	9 088 070	
with expanding sockets	$\varnothing 10 \times 11$	9 088 082	

Without Silent System, with self closing feature (Sensys 8639 W30)

Cup assembly	Mounting hole $\varnothing \times T$ mm	overlay	inset
		50 ea.	50 ea.
For screwing on	-	9 088 100	9 088 101
Fix fast assembly	$\varnothing 10 \times 6$	9 088 136	

Without Silent System, without self closing feature, for handleless applications (Sensys 8669 W30)

Cup assembly	Mounting hole $\varnothing \times T$ mm	overlay	inset
		50 ea.	50 ea.
For screwing on	-	9 088 176	9 088 177
Fix fast assembly	$\varnothing 10 \times 6$	9 088 212	