


## Fast assembly concealed hinge

- ▶ Sensys angle hinge W30
- ▶ Opening angle 95°, drilling pattern TH 52 x 5.5 mm



- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness 15 - 28 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated overlay adjustment +2 mm / -2 mm
- ▶ Integrated depth adjustment +3 mm / -2 mm
- ▶ Height adjustment at mounting plate
- ▶ Steel / nickel plated die-cast zinc

Drilling pattern



overlay  
(Base B 2 mm)



inset  
(Base B -16 mm)



### With integrated Silent System, with self closing feature (Sensys 8639i W30)

Mounting option	Mounting hole ø x T mm	overlay 50 ea.	inset 50 ea.
for screwing on	-	<b>9 088 016</b>	<b>9 088 017</b>
for pressing in	ø 10 x 11	<b>9 088 034</b>	
Fix fast assembly	ø 10 x 6	<b>9 088 070</b>	

### Without Silent System, with self closing feature (Sensys 8639 W30)

Mounting option	Mounting hole ø x T mm	overlay 50 ea.	inset 50 ea.
for screwing on	-	<b>9 088 100</b>	<b>9 088 101</b>
Fix fast assembly	ø 10 x 6	<b>9 088 136</b>	

### Without Silent System, without self closing feature, for handleless applications (Sensys 8669 W30)

Mounting option	Mounting hole ø x T mm	overlay 50 ea.	inset 50 ea.
for screwing on	-	<b>9 088 176</b>	<b>9 088 177</b>
Fix fast assembly	ø 10 x 6	<b>9 088 212</b>	



[hettich.com/short/61b351](https://hettich.com/short/61b351)