

Fast assembly concealed hinge

- ▶ Sensys angle hinge W45
- ▶ Opening angle 95°, drilling pattern TH 52 x 5.5 mm



- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness 15 - 28 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated overlay adjustment +2 mm / -2 mm
- ▶ Integrated depth adjustment +3 mm / -2 mm
- ▶ Height adjustment at mounting plate
- ▶ Steel/nickel plated die-cast zinc

Drilling pattern	overlay (Base B 9 mm)	overlay (Base B -2 mm)	inset (Base B -25 mm)

With integrated Silent System, with self closing feature (Sensys 8639i W45)

Mounting option	Mounting hole ø x T mm	overlay		inset
		Base B 9 mm 50 ea.	Base B -2 mm 50 ea.	Base B -25 mm 50 ea.
for screwing on	-	9 088 018	9 088 019	9 088 020
for pressing in	ø 10 x 11	9 088 036	9 088 037	
Fix fast assembly	ø 10 x 6	9 088 072	9 088 073	

Without Silent System, with self closing feature (Sensys 8639 W45)

Mounting option	Mounting hole ø x T mm	overlay		inset
		Base B 9 mm 50 ea.	Base B -2 mm 50 ea.	Base B -25 mm 50 ea.
for screwing on	-	9 088 102	9 088 103	9 088 104
Fix fast assembly	ø 10 x 6	9 088 138	9 088 139	

Without Silent System, without self closing feature, for handleless applications (Sensys 8669 W45)

Mounting option	Mounting hole ø x T mm	overlay		inset
		Base B 9 mm 50 ea.	Base B -2 mm 50 ea.	Base B -25 mm 50 ea.
for screwing on	-	9 088 178	9 088 179	9 088 180
Fix fast assembly	ø 10 x 6	9 088 214	9 088 215	



hettich.com/short/44e397