


## 02 Zagen en oscilleren

Kleurcodering					
Materiaal			<b>Fe</b>	<b>Al</b>	
Aanbevolen toerentalniveau	<b>3-6</b>	<b>3-5</b>	<b>2-4</b>	<b>3-6</b>	<b>4-6</b>

### ALUMINIUM/ PLASTICS



	Diameter	Zaagbreedte	Asgat-Ø	Aantal tanden	Spaanhoek	Tandvorm	VAP €* 147,86	Bestel-Nr.
HW 160x1,8x20 F/FA52	160 mm	1,8 mm	20 mm	52	-5°	F/FA	<b>122,20</b> 147,86	205555
HW 160x2,2x20 TF52	160 mm	2,2 mm	20 mm	52	-5°	TF	<b>122,20</b> 147,86	496306
HW 190x2,6 FF TF58	190 mm	2,6 mm	FF**	58	-5°	TF	<b>154,50</b> 186,95	492051
HW 210x2,4x30 TF72	210 mm	2,4 mm	30 mm	72	-5°	TF	<b>182,60</b> 220,95	493201
HW 216x2,3x30 W60	216 mm	2,3 mm	30 mm	60	-5°	W	<b>172,80</b> 209,09	491051
HW 216x2,3x30 TF64	216 mm	2,3 mm	30 mm	64	0°	TF	<b>172,80</b> 209,09	500122
HW 225x2,6x30 TF68	225 mm	2,6 mm	30 mm	68	-5°	TF	<b>179,10</b> 216,71	488291
HW 230x2,5x30 TF76	230 mm	2,5 mm	30 mm	76	-5°	TF	<b>176,00</b> 212,96	500649
HW 254x2,4x30 TF80 A	254 mm	2,4 mm	30 mm	80	-5°	TF	<b>165,70</b> 200,50	575978
HW 260x2,4x30 TF68	260 mm	2,4 mm	30 mm	68	0°	TF	<b>182,10</b> 220,34	494607

### LAMINATE/ HPL



HW 160x1,8x20 TF52	160 mm	1,8 mm	20 mm	52	-5°	TF	<b>122,20</b> 147,86	205554
HW 160x2,2x20 TF48	160 mm	2,2 mm	20 mm	48	4°	TF	<b>122,20</b> 147,86	496308
HW 190x2,6 FF TF54	190 mm	2,6 mm	FF**	54	4°	TF	<b>154,50</b> 186,95	492052
HW 210x2,4x30 TF60	210 mm	2,4 mm	30 mm	60	4°	TF	<b>182,60</b> 220,95	493200
HW 216x2,3x30 WZ/FA60	216 mm	2,3 mm	30 mm	60	-5°	WZ/FA	<b>172,80</b> 209,09	500123
HW 225x2,6x30 TF64	225 mm	2,6 mm	30 mm	64	4°	TF	<b>179,10</b> 216,71	489459
HW 254x2,4x30 TF80 L	254 mm	2,4 mm	30 mm	80	4°	TF	<b>165,70</b> 200,50	575977
HW 260x2,5x30 WZ/FA64	260 mm	2,5 mm	30 mm	64	-5°	WZ/FA	<b>182,10</b> 220,34	494606

### STEEL



HW 210x2,2x30 F36	210 mm	2,2 mm	30 mm	36	1°	F	<b>127,50</b> 154,28	493351
HW 230x2,5x30 F48	230 mm	2,5 mm	30 mm	48	0°	F	<b>123,30</b> 149,19	500651

### ABRASIVE MATERIALS



DIA 160x1,8x20 F4 Zaagblad uitsluitend voor TS 55 F en TS 55 K geschikt	160 mm	1,8 mm	20 mm	4	10°	F	<b>153,20</b> 185,37	205558
DIA 160x2,2x20 F4 Zaagblad uitsluitend voor TS 55 R en TSC 55 geschikt	160 mm	2,2 mm	20 mm	4	10°	F	<b>166,10</b> 200,98	201910

Aanbevolen toerentalniveau